




This grate is part of ACO's Heelsafe® Anti-Slip range. For more information visit www.heelsafe.com.au

Product Features

- Certified to AS 3996 Load Class A (10kN) (NATA endorsed load test reports available)
- AS 3996 (Clause 3.3.6) compliant for surface openings in pedestrian areas
ASME A112.6.3 (Section 7.12) compliant - American high heel standard
- AS 4586: P4 – Slip resistance classification for Wet Pendulum Test
AS 4586: C/B¹ - Slip resistance classification for Wet-Barefoot Inclining Platform Test
AS 4586: R9/R10¹ - Slip resistance classification for Oil-Wet Inclining Platform Test
- AS 1428.1 (Clause 4.4c)² compliant for wheelchair and walking cane safety
- AS 3996 (Clause 3.3.7) compliant for bicycle tyre penetration resistance

- Raised pattern and nodes for tread durability
- Corrosion resistant
- **DrainLok** barless and boltless locking system
- Suitable for use with K100, KS100, H100K, H100KS channels
- Manufactured from durable, UV stable polypropylene

¹ Test direction (perpendicular/parallel) relative to the grate's length (NATA endorsed test reports available)
² Dominate direction of travel perpendicular to the grate's length



Specifications

The grate shall be ACO Type 494D/495D* Black/Grey* Plastic Intercept Heelsafe® Anti-Slip grate with DrainLok barless and boltless locking system as manufactured by ACO. This grate has an overall width of 123mm and overall length of 500mm. Slot widths measure at a maximum of 9mm.

Materials & Design

The grate shall be manufactured from polypropylene and have **minimum** properties and characteristics as follows:

- Raised pattern and nodes for tread durability
- Corrosion resistant
- Manufactured from UV stable polypropylene
- Certified to AS 3996 Load Class A (10kN)²
- AS 4586: P4 – Slip resistance classification for Wet Pendulum Test²
- AS 4586: C/B¹ - Slip resistance classification for Wet-Barefoot Inclining Platform Test²
- AS 4586: R9/R10¹ – Slip resistance classification for Oil-Wet Inclining Platform Test²
- Meets AS 1428.1 (Clause 4.4c)³; AS 3996 (Clause 3.3.6 & 3.3.7); ASME A112.6.3 (Section 7.12)
- Intake area of 18,065mm² per half metre of grate

¹ Test direction (perpendicular/parallel) relative to the grate's length
² NATA endorsed test reports available
³ Dominate direction of travel perpendicular to the grate's length

For the specification of the ACO Drain channel system selected, click: <http://www.acodrain.com.au/product-support>

ACO Specification Information




ACO DRAIN®


Type 494D/495D Black/Grey Plastic Intercept Heelsafe® Anti-Slip grate



Plan view




Side elevation



Description	Part No.	Length (mm)	Width (mm)	Weight (kg)
DrainLok grate				
Type 494D Black Plastic Intercept Heelsafe® Anti-Slip	142459	500	123	0.8
Type 495D Grey Plastic Intercept Heelsafe® Anti-Slip	142460	500	123	0.8
Grate removal tool	01318	-	-	0.1

'DrainLok' locking mechanism



ACO DrainLok™ is a patented, boltless locking system that removes the need for bolts and bars and improves the hydraulic capacity of the channel. The DrainLok™ mechanism simply clips into the channel edge rail for rapid installation. ACO DrainLok™ grates are fitted with an anti-shunt mechanism that restricts unwanted grate movement when installed, improving durability and longevity of the system.

ACO Pty Ltd
Australia
Ph: 1300 765 226
www.acodrain.com.au
sales@acoaus.com.au

ACO Limited
New Zealand
Ph: 0800 448 080
www.acodrain.co.nz
sales@aconz.co.nz



© January 2022 ACO Pty Ltd. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.